



## ENCLOSURE

### CABINET

#### 316 STAINLESS STEEL ENCLOSURE WITH RAIN ROOF



#### 316 Stainless Steel Enclosure 400Hx-400Wx200D 30 Degree Sloping Roof

##### Includes:

- Insect screened ventilation top & bottom alternate sides
- Powder Coated backing board
- All wiring
- Glands
- Fuses
- Ducting
- Wiring diagram
- Optional front panel display

##### SOLAR POWER SUPPLY

- Solar panel 12V - 20W
- Solar regulator - 12V 6A
- Batteries - 12V 28Ah Sealed Lead Acid
- Solar panel frame and clamps

### TELEMETRY

#### GSM PACKET DATA



Packet Data 3G/4G Modem with Ethernet Port connectivity to Campbell CR1000X Proven in Indonesia.

Network Technology	4G with automatic fallback to 3G and 2G).
RF Connectors	3 female SMA jacks (for primary cellular and optional diversity cellular and GPS).
Operating Temperature Range	-30° to +70
Host Interface	> 10/100/1000 Ethernet RJ45 > RS-232 Serial DTE D89 Female > USB 2.0 Micro-8
Dimensions	11.9 x 9.4 x 3.4 cm (4.69 x 3.7 x 1.34 in)
Weight	320 b (11.3 oz)